



## C0067X HYPERCELL

HPL N female connector

### GENERAL CHARACTERISTICS

Inner Conductor:	Silver - plated bronze
Dielectric:	PTFE
Body:	Copper alloy - plated brass
Clamping and Coupling Nut:	Nickel - plated brass
Clamping Nut Waterproof:	Silicone O-ring

### MECHANICAL & ENVIRONMENTAL

Interface Durability:	500 cycles	
Temperature:	Operating	-40°C / +85°C
	Storage	-40°C / +85°C
Weight:	690 g	
Waterproof Index:	IP68	
RoHS Compliance:	Yes	

## ELECTRICAL

Impedance:	$50 \pm 1 \Omega$
Operating Frequency Band:	DC ~ 2.5 GHz
VSWR:	0 ~ 2.2 GHz : $\leq 1.10$
	2.2 ~ 3 GHz : $\leq 1.15$
3rd Order Passive Intermodulation, Measured In Swept Frequency Mode with 2x20W carriers, F $\leq$ 1880 MHz:	$\leq -145$ dBc
Voltage Test (at sea level):	2500 V eff / 50 Hz
Operating Voltage (at sea level):	1500 V eff / 50 Hz
Insulation Resistance:	$\geq 5000 M\Omega$
Contact Resistance:	Inner contact: $\leq 1.5 m\Omega$
	Outer contact: $\leq 1.0 m\Omega$

## RANGE

Compatibility with ACOME HPL 50 -1-5/8

M2939, M2940

Test Methods: IEC 61169, IEC 62037, IEC 60529

## RECOMMENDATIONS

### INSTALLATION INSTRUCTION

ANM - C0067X