



C1394E-L150 HYPERCELL

Jumper 3/8SF PE N male - N male

GENERAL CHARACTERISTICS

Cable:	ACOME 50-3/8SF PE cable
Connector:	N male
Assembly:	Inner and outer contact 100% soldered and with thermal shrink tube

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	2.5 N.m Max.
Minimum Bending Radius:	25 mm

ENVIRONMENTAL

Operating Temperature Range:	$-55^{\circ}\text{C} < \theta < +70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

ELECTRICAL

Impedance:	50 ± 1Ω			
Operating Frequency Range:	DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):	0.51 KW			
Velocity:	83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2× 20W Carriers:	IM3 at 900MHz	≤ -160 dBc		
	IM3 at 1800MHz	≤ -160 dBc	IM7 at 2100MHz	≤ -160 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
0.7	C1394E-L70	225	-32	0.21	-30	0.32	-26	0.38
0.8	C1394E-L80	235	-32	0.23	-30	0.35	-26	0.41
1	C1394E-L100	260	-32	0.25	-30	0.38	-26	0.45
1.5	C1394E-L150	325	-32	0.33	-30	0.48	-26	0.58
2	C1394E-L200	390	-32	0.38	-30	0.59	-26	0.70
2.5	C1394E-L250	450	-32	0.46	-30	0.70	-26	0.83
3	C1394E-L300	515	-32	0.53	-30	0.80	-26	0.95
4	C1394E-L400	640	-32	0.67	-30	1.01	-26	1.20
5	C1394E-L500	770	-32	0.81	-30	1.22	-26	1.45