



C1394E-L150 HYPERCELL

Jumper 3/8SF PE N male - N male

GENERAL CHARACTERISTICS

| | |
|------------|--|
| Cable: | ACOME 50-3/8SF PE cable |
| Connector: | N male |
| Assembly: | Inner and outer contact 100% soldered and with thermal shrink tube |

MECHANICAL & ENVIRONMENTAL

| | |
|---|-----------------------------|
| Material and Finish of Connector Body: | Copper alloy - plated brass |
| Material and Finish of Coupling Nut: | Nickel - plated brass |
| Material and Finish of Inner Conductor: | Silver - plated bronze |
| Coupling Waterproof: | Silicone Rubber O-ring |
| Coupling Torque: | 2.5 N.m Max. |
| Minimum Bending Radius: | 25 mm |

ENVIRONMENTAL

| | |
|------------------------------|--|
| Operating Temperature Range: | $-55^{\circ}\text{C} < \theta < +70^{\circ}\text{C}$ |
| Waterproof Index: | IP68 (1m /24 h) |
| RoHS Compliance: | Yes |
| Test Methods: | IEC 61169, IEC 60529 |

ELECTRICAL

| | | | | |
|---|----------------|------------|----------------|------------|
| Impedance: | 50 ± 1Ω | | | |
| Operating Frequency Range: | DC ~ 3GHz | | | |
| RMS Power (40 °C - 2 GHz): | 0.51 KW | | | |
| Velocity: | 83% | | | |
| Passive Intermodulation Measured In Swept Frequency Mode, With 2× 20W Carriers: | IM3 at 900MHz | ≤ -160 dBc | | |
| | IM3 at 1800MHz | ≤ -160 dBc | IM7 at 2100MHz | ≤ -160 dBc |

RANGE

| Length (m) | Product number | Weight (g) | Frequency 0/1000MHz | | Frequency 1000/2200MHz | | Frequency 2200/3000MHz | |
|------------|----------------|------------|---------------------|----------|------------------------|----------|------------------------|----------|
| | | | RL (dB) | ATT (dB) | RL (dB) | ATT (dB) | RL (dB) | ATT (dB) |
| 0.7 | C1394E-L70 | 225 | -32 | 0.21 | -30 | 0.32 | -26 | 0.38 |
| 0.8 | C1394E-L80 | 235 | -32 | 0.23 | -30 | 0.35 | -26 | 0.41 |
| 1 | C1394E-L100 | 260 | -32 | 0.25 | -30 | 0.38 | -26 | 0.45 |
| 1.5 | C1394E-L150 | 325 | -32 | 0.33 | -30 | 0.48 | -26 | 0.58 |
| 2 | C1394E-L200 | 390 | -32 | 0.38 | -30 | 0.59 | -26 | 0.70 |
| 2.5 | C1394E-L250 | 450 | -32 | 0.46 | -30 | 0.70 | -26 | 0.83 |
| 3 | C1394E-L300 | 515 | -32 | 0.53 | -30 | 0.80 | -26 | 0.95 |
| 4 | C1394E-L400 | 640 | -32 | 0.67 | -30 | 1.01 | -26 | 1.20 |
| 5 | C1394E-L500 | 770 | -32 | 0.81 | -30 | 1.22 | -26 | 1.45 |