



C5927E-L500 HYPERCELL

Jumper 3/8SF PE 7/16 Din Male - N Female

GENERAL CHARACTERISTICS

| | |
|------------|--|
| Cable: | ACOME 50-3/8SF PE cable |
| Connector: | 7/16 Din male / N female |
| Assembly: | Inner and outer contact 100% soldered and with thermal shrink tube |

MECHANICAL & ENVIRONMENTAL

| | | |
|---|-----------------------------|--------------|
| Material and Finish of Connector Body: | Copper alloy - plated brass | |
| Material and Finish of Coupling Nut: | Nickel - plated brass | |
| Material and Finish of Inner Conductor: | Silver - plated bronze | |
| Coupling Waterproof: | Silicone Rubber O-ring | |
| Coupling Torque: | N interface | 2.5 N.m Max. |
| | Din interface | 30 N.m Max. |
| Minimum Bending Radius: | 25 mm | |

ENVIRONMENTAL

| | |
|------------------------------|---------------------------|
| Operating Temperature Range: | -55°C < θ < + 70°C |
| Waterproof Index: | IP68 (1m /24 h) |
| RoHS Compliance: | Yes |
| Test Methods: | IEC 61169, IEC 60529 |

ELECTRICAL

| | | | | |
|--|----------------|------------|----------------|------------|
| Impedance: | 50 ± 1Ω | | | |
| Operating Frequency Range: | DC ~ 3GHz | | | |
| RMS Power (40 °C - 2 GHz): | 0.51 KW | | | |
| Velocity: | 83% | | | |
| Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carriers: | IM3 at 900MHz | ≤ -160 dBc | | |
| | IM3 at 1800MHz | ≤ -160 dBc | IM7 at 2100MHz | ≤ -160 dBc |

RANGE

| Length (m) | Product number | Weight (g) | Frequency 0/1000MHz | | Frequency 1000/2200MHz | | Frequency 2200/3000MHz | |
|------------|----------------|------------|---------------------|----------|------------------------|----------|------------------------|----------|
| | | | RL (dB) | ATT (dB) | RL (dB) | ATT (dB) | RL (dB) | ATT (dB) |
| 2 | C5927E-L200 | 415 | -32 | 0.39 | -30 | 0.59 | -26 | 0.70 |
| 3 | C5927E-L300 | 545 | -32 | 0.53 | -30 | 0.80 | -26 | 0.95 |
| 5 | C5927E-L500 | 800 | -32 | 0.81 | -30 | 1.22 | -26 | 1.45 |