



C0761E HYPERCELL

Jumper 1/2F PE 7/16 Din Female - 7/16 Din Female

GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2F PE cable
Connector:	7/16 Din female
Assembly:	Inner and outer contact 100% soldered and with molding

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	30 N.m Max.
Minimum Bending Radius:	70 mm

ENVIRONMENTAL

Operating Temperature Range:	-55°C < θ < + 70°C
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 62037, IEC 60529

ELECTRICAL

Impedance:	50 ± 1Ω			
Operating Frequency Range:	DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):	0.81 KW			
Velocity:	87%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carriers:	IM3 at 900MHz	≤ -160 dBc		
	IM3 at 1800MHz	≤ -160 dBc	IM7 at 2100MHz	≤ -160 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
1	C0760E	390	-32	0.18	-30	0.26	-26	0.30
1.5	C0761E	505	-32	0.22	-30	0.32	-26	0.37
2	C0762E	615	-32	0.26	-30	0.38	-26	0.44
2.5	C0763E	730	-32	0.28	-30	0.43	-26	0.51
3	C0764E	840	-32	0.33	-30	0.49	-26	0.57
4	C0765E	1060	-32	0.39	-30	0.61	-26	0.71
5	C0766E	1280	-32	0.46	-30	0.71	-26	0.84