



## C2050E HYPERCELL

Jumper 1/2SF PE 7/16 Din Male - N Male

### GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF PE cable
Connector:	7/16 Din male / N male
Assembly:	Inner and outer contact 100% soldered and with molding

### MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass	
Material and Finish of Coupling Nut:	Nickel - plated brass	
Material and Finish of Inner Conductor:	Silver - plated bronze	
Coupling Waterproof:	Silicone Rubber O-ring	
Coupling Torque:	N interface	2.5 N.m Max.
	Din interface	30 N.m Max.
Minimum Bending Radius:	25 mm	

### ENVIRONMENTAL

Operating Temperature Range:	-55°C < $\theta$ < + 70°C
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

## ELECTRICAL

Impedance:	50 ± 1Ω			
Operating Frequency Range:	DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):	0.52 KW			
Velocity:	83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	≤ -160 dBc		
	IM3 at 1800MHz	≤ -160 dBc	IM7 at 2100MHz	≤ -160 dBc

## RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
0.5	C2262E	230	-32	0.16	-30	0.24	-26	0.29
1	C0311E	313	-32	0.21	-30	0.33	-26	0.37
1.5	C0293E	400	-32	0.26	-30	0.40	-26	0.47
2	C0294E	483	-32	0.33	-30	0.48	-26	0.57
3	C0295E	650	-32	0.43	-30	0.66	-26	0.78
4	C1456E	820	-32	0.55	-30	0.84	-26	1.00
5	C0906E	987	-32	0.65	-30	1.01	-26	1.20
6	C2048E	1160	-32	0.77	-30	1.19	-26	1.41
7	C2049E	1325	-30	0.88	-28	1.36	-24	1.61
8	C2050E	1495	-30	0.99	-28	1.52	-24	1.81
10	C1538E	1830	-30	1.22	-28	1.84	-24	2.19