



## C1446E HYPERCELL

Jumper 1/2SF PE 7/16 Din Male - N Male Elbow

### GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF PE cable
Connector:	7/16 Din male / N male elbow
Assembly:	Inner and outer contact 100% soldered and with thermal shrink tube

### MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass	
Material and Finish of Coupling Nut:	Nickel - plated brass	
Material and Finish of Inner Conductor:	Silver - plated bronze	
Coupling Waterproof:	Silicone Rubber O-ring	
Coupling Torque:	N interface	2.5 N.m Max.
	Din interface	30 N.m Max.
Minimum Bending Radius:	25 mm	

### ENVIRONMENTAL

Operating Temperature Range:	$-55^{\circ}\text{C} < \theta < + 70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

## ELECTRICAL

Impedance:	50 ± 1Ω			
Operating Frequency Range:	DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):	0.52 KW			
Velocity:	83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	≤ -145 dBc		
	IM3 at 1800MHz	≤ -145 dBc	IM7 at 2100MHz	≤ -145 dBc

## RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
1	C1447E	390	-28	0.22	-26	0.34	-24	0.41
2	C1448E	555	-28	0.33	-26	0.51	-24	0.61
3	C0970E	730	-28	0.44	-26	0.68	-24	0.81
4	C1449E	900	-28	0.55	-26	0.85	-24	1.01
5	C1446E	1070	-28	0.66	-26	1.02	-24	1.22