



## C1588E HYPERCELL

Jumper 1/2SF LSOH 7/16 Din Male Elbow- 7/16 Din Male

## GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF LSOH cable
Connector:	7/16 Din male elbow / 7/16 Din male
Assembly:	Inner and outer contact 100% soldered and with molding

## MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:	Copper alloy - plated brass
Material and Finish of Coupling Nut:	Nickel - plated brass
Material and Finish of Inner Conductor:	Silver - plated bronze
Coupling Waterproof:	Silicone Rubber O-ring
Coupling Torque:	30 N.m Max.
Minimum Bending Radius:	25 mm

## ENVIRONMENTAL

Operating Temperature Range:	$-40^{\circ}\text{C} < \theta < + 70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 62037, IEC 60529

## ELECTRICAL

Impedance:	50 ± 1Ω			
Operating Frequency Range:	DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):	0.52 KW			
Velocity:	83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carriers:	IM3 at 900MHz	≤ -150 dBc		
	IM3 at 1800MHz	≤ -150 dBc	IM7 at 2100MHz	≤ -150 dBc

## RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
1	C0754E	455	-28	0.22	-26	0.34	-24	0.41
1.5	C0755E	550	-28	0.28	-26	0.43	-24	0.51
2	C0756E	645	-28	0.33	-26	0.51	-24	0.61
2.5	C0757E	740	-28	0.39	-26	0.60	-24	0.71
3	C0758E	835	-28	0.44	-26	0.68	-24	0.81
3.5	C0759E	930	-28	0.51	-26	0.77	-24	0.91
4	C1588E	1025	-28	0.56	-26	0.85	-24	1.01
5	C1455E	1215	-28	0.66	-26	1.02	-24	1.21