



C0274F HYPERCELL

HPL Framework Grounding Kit

GENERAL CHARACTERISTICS

| | |
|------------------|--|
| Framework Body: | EPDM + Stainless steel |
| Grounding Cable: | Copper (0.6m length) |
| Compatibility: | Matching with the cable with copper or Aluminium outer conductor |

MECHANICAL & ENVIRONMENTAL

| | |
|-------------------|-------|
| Color: | Black |
| Waterproof Index: | IP68 |
| RoHS Compliance: | Yes |

ELECTRICAL

| | |
|----------------------------|--|
| Impact Current Resistance: | Grounding kit is able to bear or endure concussion current level reaching 70KA |
| Contact Resistance: | $\leq 5 \text{ m}\Omega$ |

RANGE

| Product number | Type | Approx. weight (g / p) |
|----------------|--|------------------------|
| C0275F | 1/4XF ($\varnothing 6.85 \times 600$) | 190 |
| C1113F | 1/4F ($\varnothing 6.85 \times 600$) | 190 |
| C0270F | 3/8XF ($\varnothing 10.1 \times 600$) | 190 |
| C1114F | 3/8F ($\varnothing 10.1 \times 600$) | 190 |
| C0271F | 1/2F ($\varnothing 16 \times 600$) | 200 |
| C0272F | 7/8F ($\varnothing 27 \times 600$) | 215 |
| C0273F | 1-1/4F ($\varnothing 39.5 \times 600$) | 245 |
| C0274F | 1-5/8F ($\varnothing 50 \times 600$) | 255 |