



C0109S HYPERCELL

HPL Single Feeder Clamp

GENERAL CHARACTERISTICS

Clamp Body:	Transnature polypropylene
Screw and Nut:	Stainless SUS304

MECHANICAL & ENVIRONMENTAL

Color:	Black
Use Temperature Range:	$-40\text{ °C} < \theta < +70\text{ °C}$
RoHS Compliance:	Yes

TYPE

Product number	Type	Approx. weight (g / p)
C1154S	1 × 1/4F (φ9.5)	155
C1155S	2 × 1/4F (φ9.5)	190
C1156S	3 × 1/4F (φ9.5)	210
C1157S	4 × 1/4F (φ9.5)	240
C1042S	1 × 3/8XF (φ10.0)	150
C1173S	2 × 3/8XF (φ10.0)	180
C1174S	3 × 3/8XF (φ10.0)	210
C1175S	4 × 3/8XF (φ10.0)	240
C1044S	1 × 3/8F (φ10.6)	168
C1176S	2 × 3/8F (φ10.6)	187
C1177S	3 × 3/8F (φ10.6)	206
C1178S	4 × 3/8F (φ10.6)	225
C0108S	1 × 1/2F (φ16)	170
C0109S	2 × 1/2F (φ16)	190
C0110S	3 × 1/2F (φ16)	220
C0781S	4 × 1/2F (φ16)	240
C0111S	1 × 7/8F (φ27)	200
C0112S	2 × 7/8F (φ27)	250
C0113S	3 × 7/8F (φ27)	310
C0655S	4 × 7/8F (φ27)	360
C0114S	1 × 1-1/4F (φ39.4)	240
C0115S	2 × 1-1/4F (φ39.4)	340
C0116S	3 × 1-1/4F (φ39.4)	430
C0782S	4 × 1-1/4F (φ39.4)	515
C0117S	1 × 1-5/8F (φ50)	280
C0118S	2 × 1-5/8F (φ50)	400
C0119S	3 × 1-5/8F (φ50)	505
C0783S	4 × 1-5/8F (φ50)	620