


R7550A-SB305 ACOLAN® COPPER

U/UTP Cat.6 400 MHz LSOH 4P ACOPACK of 305m - IVORY

APPLICATIONS

- High speed data transmission cables are designed for backbone distribution local computer networks.
- These cables are permitted the protocol supported by the class E.
- They are characterized of up to 400 MHz.
- They are compatibles with PoE & PoE+, UPoE applications.

GENERAL CHARACTERISTICS



1. Conductor	Solid annealed red copper wire, AWG 24 Colored polyethylene insulation $\square \leq 0.95$ mm
2. Cable element	Cable assembly in Twisted Pairs
3. Pair screening	Symetrical cross separator
4. Stranding	4 pairs screening assembly
5. External sheath	LSOH-FR : Low Smoke « Zero » Halogen - Flame Retardant

GENERAL

Designation ACOLAN	Ref.	Colour	Diameter	Weight	Superior calorific capacity (PCS)		Max pulling tension
			mm	Kg/km	MJ/km	KWh/m	N
400 UU 4P LSOH-FR	R7550A-S	Ivory	5.30	33	394	0.110	90

MECHANICAL

Characteristics		Values
Bending radius	Dynamic (installation)	≥ 45 mm
	Static (installed)	≥ 23 mm
Temperature range	In service	- 20°C at + 60°C
	At the installation	0°C at + 50°C
	Transport and storage	0°C at + 50°C

ELECTRICAL

Transmission characteristics at 20° C

Characteristics		Values
Complete conductor resistance		$\leq 190 \Omega / \text{km}$
Resistance unbalance		$\leq 2 \%$
Dielectric strength	Continuous current	1kV during 1 minute = No breakdown
Insulation resistance	(500 V)	$\geq 5000 \text{ M}\Omega \cdot \text{km}$
Capacitance unbalance	Real-ground	$\leq 1600 \text{ pF} / \text{km}$
Characteristic impedance	at 100 MHz	$100 \pm 5 \Omega$
Velocity	nominal	66 %
Coupling attenuation		$\geq 40 \text{ dB}$ TYPE 3
Segregation classification acc. to EN 50174-2		“c”

Frequency (MHz)		4	10	20	62.5	100	250	300**	400**	Attenuation (dB/100m)	Typical value	3.7	5.8	8.4	15.0	19.2	31.5	34.5	42	
Imposition (max)*	3.8	6	8.5	8.5	19.9	33	-	-												
Next (dB)	Typical value	69	63	59	51	48	42	41	38											
	Imposition (min)*	65.3	59.3	54.8	47.4	44.3	38.3	-	-											
ACR (dB)	Typical value	65.3	57.2	50.6	36	28.8	10.5	6.5												
	Imposition (min)*	61.5	53.3	46.3	31.9	24.4	5.3	-	-											
PS Next (dB)	Typical value	66	60	56	48	45	39	38	35											
	Imposition (min)*	63.3	57.3	52.8	45.4	42.3	36.3	-	-											
ELFEXT (dB/100 m)	Typical value	73	65	59	49	45	37	35	32											
	Imposition (min)*	58	50	44	34.1	30	22	-	-											
PS ELFEXT (dB/100 m)	Typical value	70	62	56	46	42	34	32	29											
	Imposition (min)*	55	47	41	31.1	27	19	-	-											
Return Loss (dB)	Typical value	27	27	27	25.8	25	22	22	21											
	Imposition (min)*	23	25	25	21.5	20.1	17.3	-	-											

NORMS AND STANDARDS

GENERAL



400 MHz

Applications

- IEEE 802.3: 10Base-T; 100Base-TX; 1000Base-T ;
- 1000Base-T ; 2,5G Base-T
- IEEE 802.3 af (PoE) / 802.3 at (PoE+)
- IEEE 802.5 / FDDI / ATM / RNIS

Cables

- IEC 61156-5 ed.2 / EN 50288-6-1

Cabling system standard

- ISO/IEC 11801 2nd ed. / EN 50173-1 / TIA-568.2-D

Cabling system installation standard

- EN 50174

Directive / Regulation



- RoHS 2011/65/UE
- REACH 1907/2006/EC

EUROCLASS



FIRE BEHAVIOUR

Europe

Type	Euroclass	Standards	Declaration of performance
4P	Eca	IEC 60332-1	16UUTP003  

Outside Europe

No flame propagation	IEC 60332-1 / EN 60332-1
Low smoke opacity	IEC 61034-2 / EN 61034-2
Low gas corrosivity	IEC 60754-2 / EN 60754-2
Low toxicity	IEC 60754-1 / EN 60754-1

RECOMMENDATIONS

DELIVERY LENGTH

Type	References	Individual			Expedition		
		Type	Weight	EAN code	Quantity	Weight	EAN code
4P LSOH	R7550A - SB305	Acopack of 305 m	10.70 kg	3700223681457	24 boxes	280 kg	3700223681464
	R7550A - ST1000	Drum of 1000 m	35 kg	3700223681624	18 drums	652 kg	3700223681631
	R7550A - ST4000	Drum of 4000 m	146 kg	3700223681600	1 drums	164 kg	3700223681600