



ACOPTIC - UNB1621

Indoor/outdoor strippable overhead/underground drop cable for field connectors

BENEFITS

- 2-in-1: external cable that integrates an internal subscriber line
- Tight-buffered micro-module for field connectivity
- A single cable for all applications: Overhead, Duct, Façade
- Direct connection to the OTO without disconnecting the OTB
- Quick and easy access to the subscriber line over several metres
- Micro-module venting directly in the OTB
- Compliant with CPR regulations

APPLICATIONS

- ACOME's UNB drop cable ranges have been designed to meet the needs of FTTH connections.
- The UNB1621 range connects the external connection point and the residence connection box, for the following types of installation:
 - Duct (min. 8/10mm)
 - Façade
 - Overhead for spans of 50m
- The cable buffering is adapted to using field connectors with no special tools required.
- The HDPE outer jacket can easily be removed, freeing an LSOH-FR (1) subscriber line that can then be stripped and installed via the following:
 - Laying in a cable tray
 - Gluing all the way to the subscriber's optical termination outlet

RECOMMENDATIONS

Storage and installation

- The cables are supplied with protective wrapping that must be maintained until the product has been fully used.
- The rules for storage, transport, and cable laying are described in our ACOPTIC Guide.

DOCUMENTATION

- [ACOPTIC® Guide : Cable Storage, Transport and Installation Rules](#)