



M2929Z HYPERCELL

HPL 50-1/4 SF - Black Polyethylene Jacket

GENERAL CHARACTERISTICS

Inner Conductor:	Copper - clad Aluminium Diameter: 2.5 mm
Dielectric:	Foam Polyethylene Diameter: 6.6 mm
Outer Conductor:	Corrugated copper Outer Diameter: 7.6 mm
Jacket:	Black Polyethylene Diameter: 9.5 mm

Ink marking: ACOME HYPERCELL COAX HPL 50-1/4SF SUPER FLEXIBLE M2929 LOT X lot N° (+ Metric length)

MECHANICAL

Rayon de courbure :

- Opération : 45mm-Min
- Installation : 25mm-Min
- Résistance à la traction : 500N -Max
- Poids : 71kg/km

ENVIRONMENTAL

Temperature range:

- Operating: -40°C / +85°C
- Installation: -25°C / +60°C
- Storage: -70°C / +85°C

Halogen content: IEC 60754-1

Test methods: IEC 60096-0-1, 61196-1, 60966-1

ELECTRICAL

Impedance : 50 ± 1 Ω

Return loss :

- 400 ~ 500 MHz \leq -26.5 dB
- 800 ~ 1000 MHz \leq -26.5 dB
- 1700 ~ 2200 MHz \leq -24 dB
- 2500 ~ 2700 MHz \leq -23.5 dB

Capacitance: 80 pF/m

Passive Intermodulation : \leq -158 dBc

Velocity: 83%

Dielectric constant: 1.48

Screening effectiveness: > 120 dB

Operating frequency: \leq 18 GHz

Peak power rating: 3.94 kW

Operating voltage: 0.6 kV RMS

Insulation Resistance: > 10000 M Ω .km

DC resistance:

- Inner conductor: \leq 9.78 Ω /km
- Outer conductor: \leq 6.90 Ω /km

Frequency (MHz)	Attenuation (dB/100m) @ 20°C Typical	Power kW @ 40°C-Ambient Temperature Inner conductor: 100°C
30	3.16	3.13
80	5.21	1.89
150	7.19	1.37
450	12.75	0.77
824	17.58	0.56
900	18.44	0.54
960	19.09	0.52
1000	19.53	0.50
1500	24.34	0.40
1700	26.05	0.38
1800	26.93	0.37
1900	27.70	0.36
2000	28.52	0.35
2200	30.05	0.33
2300	30.79	0.32
2400	31.50	0.31
2500	32.27	0.30
3000	35.69	0.277
3300	37.73	0.262
3400	38.36	0.258
3500	39.02	0.25
3600	39.63	0.24
3800	40.86	0.23