



## M5430Z HYPERCELL

HPL 50-7/8F ALU - Black Polyethylene Jacket

### GENERAL CHARACTERISTICS

Inner Conductor:	Copper tube Outer Diameter: 9.25 mm
Dielectric:	Foam Polyethylene Diameter: 22.4 mm
Outer Conductor:	Corrugated Aluminium Diameter over outer conductor: 25.1 mm
Jacket:	Black Polyethylene Diameter: 27.4 mm

Marking (Metric): ACOME HYPERCELL COAX HPL 50-7/8F ALU M5430 LOT X lot No. XXXXm

### MECHANICAL

Bending radius:

- Operating : 250 mm - Min
- Installation : 120 mm - Min

Tensile Strength: 1400 N - Max

Weight: 336 kg/km

## ENVIRONMENTAL

Temperature range:

- Operating: -40°C / +85°C
- Installation: -25°C / +60°C
- Storage: -70°C / +85°C

Halogen content: IEC 60754-1

Test methods: IEC 60096-0-1, 61196-1, 60966-1

## ELECTRICAL

Impedance :  $50 \pm 1 \Omega$

Return loss :

- 400 ~ 500 MHz  $\leq -26.5$  dB
- 800 ~ 1000 MHz  $\leq -26.5$  dB
- 1700 ~ 2200 MHz  $\leq -24$  dB
- 2500 ~ 2700 MHz  $\leq -23.5$  dB

Capacitance: 74 pF/m

Passive Intermodulation :  $\leq -158$  dBc

Velocity: 90%

Dielectric constant: 1.23

Screening effectiveness:  $> 120$  dB

Operating frequency:  $\leq 5$  GHz

Cut-off frequency: 5.3 GHz

Peak power rating: 90 kW

Operating voltage: 3 kV RMS

Insulation Resistance:  $> 10000$  M $\Omega$ .km

DC resistance:

- Inner conductor:  $\leq 1.72 \Omega/\text{km}$
- Outer conductor:  $\leq 1.35 \Omega/\text{km}$

Frequency (MHz)	Attenuation (dB/100m) @ 20°C Typical	Power kW @ 40°C-Ambient Temperature Inner conductor: 100°C
30	0.67	13.56
80	1.09	8.17
150	1.51	5.89
450	2.70	3.24
824	3.76	2.30
900	3.93	2.20
960	4.09	2.10
1000	4.16	2.07
1500	5.21	1.62
1700	5.58	1.50
1800	5.76	1.46
1900	5.94	1.40
2000	6.10	1.36
2200	6.43	1.29
2300	6.59	1.25
2400	6.75	1.22
2500	6.90	1.19
3000	7.64	1.06
3300	8.08	1.00
3400	8.21	0.98
3500	8.33	0.96
3600	8.46	0.94
3800	8.75	0.91