



M5430Z HYPERCELL

HPL 50-7/8F ALU - Black Polyethylene Jacket

GENERAL CHARACTERISTICS

| | |
|------------------|---|
| Inner Conductor: | Copper tube Outer Diameter: 9.25 mm |
| Dielectric: | Foam Polyethylene Diameter: 22.4 mm |
| Outer Conductor: | Corrugated Aluminium Diameter over outer conductor: 25.1 mm |
| Jacket: | Black Polyethylene Diameter: 27.4 mm |

Marking (Metric): ACOME HYPERCELL COAX HPL 50-7/8F ALU M5430 LOT X lot No. XXXXm

MECHANICAL

Bending radius:

- Operating : 250 mm - Min
- Installation : 120 mm - Min

Tensile Strength: 1400 N - Max

Weight: 336 kg/km

ENVIRONMENTAL

Temperature range:

- Operating: -40°C / +85°C
- Installation: -25°C / +60°C
- Storage: -70°C / +85°C

Halogen content: IEC 60754-1

Test methods: IEC 60096-0-1, 61196-1, 60966-1

ELECTRICAL

Impedance : $50 \pm 1 \Omega$

Return loss :

- 400 ~ 500 MHz ≤ -26.5 dB
- 800 ~ 1000 MHz ≤ -26.5 dB
- 1700 ~ 2200 MHz ≤ -24 dB
- 2500 ~ 2700 MHz ≤ -23.5 dB

Capacitance: 74 pF/m

Passive Intermodulation : ≤ -158 dBc

Velocity: 90%

Dielectric constant: 1.23

Screening effectiveness: > 120 dB

Operating frequency: ≤ 5 GHz

Cut-off frequency: 5.3 GHz

Peak power rating: 90 kW

Operating voltage: 3 kV RMS

Insulation Resistance: > 10000 M Ω .km

DC resistance:

- Inner conductor: $\leq 1.72 \Omega/\text{km}$
- Outer conductor: $\leq 1.35 \Omega/\text{km}$

| Frequency (MHz) | Attenuation (dB/100m) @ 20°C Typical | Power kW @ 40°C-Ambient Temperature Inner conductor: 100°C |
|-----------------|--------------------------------------|--|
| 30 | 0.67 | 13.56 |
| 80 | 1.09 | 8.17 |
| 150 | 1.51 | 5.89 |
| 450 | 2.70 | 3.24 |
| 824 | 3.76 | 2.30 |
| 900 | 3.93 | 2.20 |
| 960 | 4.09 | 2.10 |
| 1000 | 4.16 | 2.07 |
| 1500 | 5.21 | 1.62 |
| 1700 | 5.58 | 1.50 |
| 1800 | 5.76 | 1.46 |
| 1900 | 5.94 | 1.40 |
| 2000 | 6.10 | 1.36 |
| 2200 | 6.43 | 1.29 |
| 2300 | 6.59 | 1.25 |
| 2400 | 6.75 | 1.22 |
| 2500 | 6.90 | 1.19 |
| 3000 | 7.64 | 1.06 |
| 3300 | 8.08 | 1.00 |
| 3400 | 8.21 | 0.98 |
| 3500 | 8.33 | 0.96 |
| 3600 | 8.46 | 0.94 |
| 3800 | 8.75 | 0.91 |